

C6 Corvette Blackout installation instructions

Back Lights

Tools needed:

- T-15 Torx bit (you may be able to use a small flat head screwdriver if you don't have the Torx bit)
- 1) Clean each tail light with the alcohol pad and let dry for 10 minutes. Take off the red 3m tape backing on the blackout lens. Then with the notch facing up, press it on to the light with your thumb pressing in the center where the tape is for about 15 seconds. **(Please note this is clear 3m tape so you won't see any tape outlines when you hit your brakes or use your parking lights.)**
 - 2) Once you do this to all 4 lights you are finished. There is no wait time wash hands and admire the great new look! Don't worry this tape will hold! We tested this product with half the size of tape for about 6 months with no issues.

Removal of lens

- 1) Take your T-15 bit and remove the factory light leaving the blackout on.
- 2) Once you have removed the bulb from the back of the light and the light from the car, bring it over to a work bench or table.
- 3) Take your fingers from both hands and put them between the blackout lens and the light. Work it back and forth and all around to get it loose.
- 4) You then should be able to "POP" it off after working with it for a little. Use care not to crack the lens when removing. **DO NOT USE** anything to pry the cover off; doing so will cause damage to the lens cover and OEM light.
- 5) If you want to reinstall please see our website for the clear blackout kit re-install kit.

Thank you for your purchase and enjoy!

Greg Sanders

Sales@GSc creationsLLC.com

GSc creationsllc.com

GSCREATIONS