

# GScreations Battery Cover Install

**NOTE:** For the 2005 C6, before installing the cover test that the positive and negative cables will be routed to pass through the cutout in the cover. You may need to loosen the battery cables and rotate them.

2008+ Batteries have a special install note, please [click here](#)

**Your new cover comes to you with a protective liner. Remove liner after installation is complete.** Your cover is painted from the bottom side, please use care when installing and removing so that you do not scratch the paint.

- 1) Simply lift up and remove the passenger side half of the hood seal as shown in the picture below. (There is no need to remove it all. Place that side out of the way by laying it on the windshield)



- 2) Use the supplied alcohol pads and clean the battery where the Velcro is going to make contact. Let dry for 3 mins.

3) Remove the paper backing from both pieces of Velcro and use care to not let them touch the battery or any part of the car until in its final resting place. **(Its suggested you test fit your cover before removing the backing so you can familiarize yourself with the install procedure)**

4) Hold the cover over the battery, tilt and slip the top left corner of the battery cover under the hood latch and towards the rear left of the battery. Lay battery cover flat and be sure you apply pressure on the cover on the two spots where the Velcro is installed. Do not remove battery cover for at least 24 hours to let the Velcro adhere to the battery. Replace the hood seal from step one and you are DONE!

#### **2005 Battery Cover shown below**



**2008 Battery Cover Shown Below**





GScreationsLLC.com

## 2008+ Batteries

GM changed the design of the battery starting in 2008, they used a larger battery. The positive cable is routed to the side of the battery so you will need to slide your battery over about 2". Try to slide it over by applying light pressure, if there is no movement, loosen the battery hold down screw just enough to be able to slide the batter cover. Be sure to tighten the screw back once in final location.

Once this had been done please follow the normal [install procedure above](#)

Thank you for your purchase and enjoy!

GS Creations, LLC

[www.GSCreationsllc.com](http://www.GSCreationsllc.com)

(We can get you ANY GM part for way under dealer cost!!!

Just email us with what part you need)

